



Specifications Noxion LED Downlight  
Apollo 9W 1100lm 60D - 840 Cool  
White | 145mm - Cutout 120mm - UGR  
<19



[View Product](#)

## General Information

|                          |                                                                           |
|--------------------------|---------------------------------------------------------------------------|
| SKU                      | 243079                                                                    |
| EAN                      | 8719157034982                                                             |
| manufacturer_code        | 8719157034982                                                             |
| Brand                    | Noxion                                                                    |
| Manufacturer Name        | Noxion LED Downlight Apollo 9W 1200LM 4000K Cutout Ø120mm<br>Frame Ø145mm |
| Any Lamp all-in warranty | 6 Years                                                                   |
| Average Lifetime (h)     | 60000                                                                     |

## Technical Information

|                             |                   |
|-----------------------------|-------------------|
| Emergency Lighting          | No Emergency Unit |
| Tiltable                    | No                |
| Technology                  | LED Integrated    |
| Replaces (Watt)             | 18                |
| Wattage                     | 9W                |
| Voltage (V)                 | 220-240           |
| Dimmable                    | Not Dimmable      |
| Colour Code                 | 840 Cool White    |
| Colour temperature (Kelvin) | 4000 Cool White   |
| Colour Rendering (Ra)       | 80-89             |
| Colour of Light             | White             |

|                         |                                |
|-------------------------|--------------------------------|
| Light Colour Options    | Single Color                   |
| Including bulb          | Yes                            |
| Driver Included         | Yes                            |
| Beam Angle (degree)     | 60                             |
| Luminous Flux (Lumen)   | 1100lm                         |
| Lumen per watt          | 125                            |
| Power factor            | >0.90                          |
| Installation Depth (mm) | 89                             |
| Unified Glare Rating    | < 19 - for offices and schools |
| Optical Cover           | PC (Polycarbonate)             |
| Finish of Reflector     | PC (Polycarbonate)             |
| Product Type Category   | LED Downlight                  |

## Fixture Information

|                        |                   |
|------------------------|-------------------|
| Mounting Method        | Recessed          |
| Cut out (mm)           | 120               |
| IP-Rating              | IP20              |
| Impact Protection (IK) | IK03 - 0.35 joule |
| Operating Temperature  | -20 to +40        |
| Housing                | Aluminium         |
| Colour of the Fixture  | White             |
| Colour of material     | White             |
| Series                 | Apollo            |

## Dimensions

|               |     |
|---------------|-----|
| Height (mm)   | 89  |
| Diameter (mm) | 145 |

## Sensor Information

---

Type of sensor

No Sensor

## Why Any-lamp?



Order from the **largest lighting specialist** in Europe



**Customised** quotation



Up to **7 years warranty**



**Easy** return process

